



Subject to modifications.

GEA Ariete Homogenizer 5315

Technical data | Homogenizer & High Pressure Pump

The Ariete Series is the state-of-the-art for powerful reliable high pressure machines and customized solutions. The Ariete machines, compliant to EU safety rules (CE standards) and built according to EN ISO 9001:2008 Quality System, are the best fit for pharmaceutical, dairy, food & beverage, biotech, chemical and cosmetics industries.

Suitable for CIP and SIP, the Ariete Series can be supplied with all necessary customizations for easy integration in any process line. The wide range of available materials, the low running speed (max. 185 rpm) and linear plunger velocity allow Ariete machines to perform at their best also on abrasive and viscous product.

Main options

- 2nd stage homogenizing valve
- Electric power board for fixed or variable capacity
- Machine automation and remote controls
- Aseptic execution
- 3-A execution
- FDA approved gaskets and cGMP documentation
- Automatic front door opening system
- Double inlet manifold

Sustainability options

- NanoVALVE™
- Oil Purification System
- NiSoPURE

Sustainability values

Energy consumption/1000 l product (kWh)	4,5
Water consumption/1000 l product (l)	6,6
Lubricating and cooling water	430 l/h
Oil consumption ISO VG 150	95 l/2.000 h
Noise level	≤85 dB(A) ± 2
Carbon footprint/1000 l product (kg CO2)	2,29

Technical data

Number of plungers	5
Absorbed motor power up to	315 kW
Net weight	8.800 kg
Gross weight	6.500 kg

Process data

Sanitary execution: max. capacity at 150 bar; water max. hardness <15°fH, max. particle size 60 microns, filtered water; noise level at max. capacity and max. pressure at 1 meter distance; CO2 emissions based on electricity production generating 0,5 kg CO2/kWh.

Technical data | Homogenizer & High Pressure Pump

Liquid end

- High quality stainless steel and special high wear resistant materials for best mechanical and corrosion resistance performance
- 3-A and electropolished versions available
- Ball (PVB) and poppet valves (PVP) interchangeable into the same block design for maximum product handling flexibility
- Aseptic version compression block available as option, with sterile condensate packing flushing
- Various materials for pumping plungers
- Monoblock construction up to 600 bar, forged high grade Duplex or Super Duplex SS alloy

Homogenizing valve

- One stage (standard on homogenizers) with pneumatic adjustment from the machine's control panel
- NanoVALVE™, high efficiency homogenizing valves, available as option
- Engineered for easy maintenance and cleaning
- Second stage as option

Power end

- Rugged cast iron power frame
- Heavy duty and reliable power frame housing the transmission elements with integrated planetary gearbox
- "V" belts drive and gearbox speed reduction unit
- AC motor drive
- Forced lubrication with gear pump, low oil pressure switch and oil cooling

Casing

- Made of polished stainless steel with sound proof lining with noise reduction execution
- Inlet manifold fitted inside case ensures considerable noise reduction
- Easy access and maintenance with removable panels
- Fully separated liquid-end from drive end
- Large front doors offer a full visibility of the process part

Plungers

- Chrome coated stainless steel
- Tungsten carbide coated stainless steel
- Solid ceramic and HCR Chromium Carbide coated stainless steel

Pump valves

- High wear resistant Stellite™ alloy removable seats
- Ball type (PVB) or poppet type (PVP) in solid Stellite™
- Tungsten carbide materials available as option

Pressure measurement & control

- Sanitary design analog high pressure gauge
- Pressure transmitters and transducers available as option

Safety devices

- Overpressure relief valve installed on the compression block available as option in different versions according to customer applications
- Emergency push button with reset
- Stainless steel compression head cover

Product line connections


- DIN 11851, Tri-Clamp™, GEA Tuchenhagen Varivent™
- Others as option upon request

Tools and spare parts

- Ordinary maintenance tools and one set of emergency spare parts supplied with the machine
- O&M manual and spare part list on USB stick

Dimensional drawing

Overall dimensions (mm)



Performance	
Pressure (bar)	Max Flow Rate (l/h)
100	65.000
150	55.000
180	47.000
200	41.000
250	34.000

Performance	
Pressure (bar)	Max Flow Rate (l/h)
300	28.000
400	21.000
500	17.000
600	14.000

Each line refers to a different machine, which is designed for the specified maximum pressure and maximum capacity in the above table.

GEA Mechanical Equipment Italia S.p.A.

Via A.M. Da Erba Edoari, 29
43123 Parma, Italy

Tel +39 0521 965411
gea.com/contact